

P/N NAS1200M6-4

Military-Fasteners.com

Description

diameter: 3/16" length: 1/4", solid rivet - 100°, flush shear head - monel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1200M64
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-391-9190
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



P/N NAS1200M6-4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.297 Inches Minimum And 0.298 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Monel (uns N04400) Mfr Ref Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/solid+rivets/NAS1200M6-4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.