

P/N NAS1200M6-7

Description

diameter: 3/16" length: 7/16", solid rivet - 100°, flush shear head - monel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1200M67

Minimum Qty (MOQ): 1 Pound

NSN: 5320-01-068-5543

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



^{*} See page 2 for technical characteristics

P/N NAS1200M6-7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.3016 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281,cl A Fed Spec Single Material Response Overall
Specification/standard Data:	80205-nas1200 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/NAS1200M6-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.