

**Description**


length: 0.714", thread: 8-32, close tolerance, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS12027                                  |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5305-00-086-2454                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1202-7 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.251 Inches Minimum And 0.301 Inches Maximum  |
| <b>Fastener Length:</b>                               | 0.699 Inches Minimum And 0.729 Inches Maximum  |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.280 Inches Minimum And 0.337 Inches Maximum  |
| <b>Grip Diameter:</b>                                 | 0.1625 Inches Minimum And 0.1635 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                       | 0.164 Inches   |
| <b>Grip Length:</b>                                   | 0.428 Inches Minimum And 0.448 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjc   |
| <b>Specification/standard Data:</b>                   | 80205-nas1202 Professional/industrial Association Standard   |

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1202-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.