

Description

length: 1.151", thread: 10-32, close tolerance bolt, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS120314 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-00-721-3059 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N NAS1203-14 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.276 Inches Minimum |
| Fastener Length: | 1.151 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.376 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740 |
| Screw Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response |
| Screw Surface Treatment: | Cadmium |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1203 Professional/industrial Association Standard |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1203-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.