

## **P/N NAS1203-7**

### **Description**

length: 0.714", thread: 10-32, close tolerance, head, cadmium plated alloy steel, NAS1203 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS12037

Minimum Qty (MOQ): 100

NSN: 5305-00-754-2064

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N NAS1203-7 Specifications

| 3a   |
|--|
| Right-hand   |
| 0.276 Inches Minimum   |
| 0.699 Inches Minimum And 0.729 Inches Maximum  |
| Flat Countersunk   |
| 0.328 Inches Minimum And 0.375 Inches Maximum  |
| 0.1885 Inches Minimum And 0.1895 Inches Maximum  |
| Cross Recess Type 1  |
| 0.190 Inches   |
| 0.438 Inches Nominal   |
| 32   |
| 160000 Pounds Per Square Inch  |
| 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  |
| 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall |
| Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd    |
| Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  |
| Cadmium Overall And Chromate Overall   |
| Qq-p-416,ty2 Cl3 Fed Spec Single Treatment Response Overall  |
| Unf  |
| 80205-nas1203 Professional/industrial Association Standard   |
|  |

## **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1203-7">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1203-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.