

## **P/N NAS1204-10D**

### **Description**

drilled shank - length: 0.941", thread: 1/4-28, close tolerance bolt - 100°, head - cadmium plated alloy steel"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS120410D

Minimum Qty (MOQ): 10

NSN: 5305-00-884-1375

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1204-10D Specifications

| - La  |   |
|---|---|
| Thread Class:   | 3a  |
| Thread Direction:   | Right-hand  |
| Thread Length:  | 0.316 Inches Minimum  |
| Fastener Length:  | 0.926 Inches Minimum And 0.956 Inches Maximum   |
| Head Style:   | Flat Countersunk  |
| Head Diameter:  | 0.449 Inches Minimum And 0.507 Inches Maximum   |
| Grip Diameter:  | 0.2485 Inches Minimum And 0.2495 Inches Maximum   |
| Shank Unthreaded Hole Diameter:                                     | 0.076 Inches Nominal First Hole   |
| Internal Drive Style:   | Cross Recess Type 1   |
| Nominal Thread Diameter:  | 0.250 Inches  |
| Grip Length:  | 0.625 Inches Nominal  |
| Thread Quantity Per Inch:   | 28  |
| Minimum Tensile Strength:   | 160000 Pounds Per Square Inch   |
| Hardness Rating:  | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall   |
| Countersink Angle:  | 99.0 Degrees Minimum And 101.0 Degrees Maximum  |
| Distance From Head Largest Bearing<br>Surface To Shank Hole Center: | 0.825 Inches Nominal First Hole   |
| Material:   | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  |
| Material Document And Classification:                               | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Surface Treatment:  | Cadmium Overall And Chromate Overall  |
| Surface Treatment Document And Classification:                      | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall  |
| Thread Series Designator:   | Unf   |
| Specification/standard Data:  | 80205-nas1204 Professional/industrial Association Standard  |
|   |   |

## **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1204-10D">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1204-10D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.