

P/N NAS1204-5

Description

length: 0.628", thread: 1/4-28, close tolerance, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information


SKU / Model: NAS12045

Minimum Qty (MOQ): 100

NSN: 5305-00-815-5050

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS1204-5 Specifications

3a
Right-hand
0.291 Inches Minimum And 0.341 Inches Maximum
0.613 Inches Minimum And 0.643 Inches Maximum
Flat Countersunk
0.449 Inches Minimum And 0.507 Inches Maximum
0.2485 Inches Minimum And 0.2495 Inches Maximum
Cross Recess Type 1
0.250 Inches
0.302 Inches Minimum And 0.322 Inches Maximum
28
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd
Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1204 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1204-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.