

P/N NAS1204-6

Description

length: 0.691", thread: 1/4-28, close tolerance, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS12046

Minimum Qty (MOQ): 50

NSN: 5305-00-721-3060

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1204-6 Specifications

3a
Right-hand
0.316 Inches Minimum
0.676 Inches Minimum And 0.706 Inches Maximum
Flat Countersunk
0.449 Inches Minimum And 0.507 Inches Maximum
0.2485 Inches Minimum And 0.2495 Inches Maximum
Cross Recess Type 1
0.250 Inches
0.375 Inches Nominal
28
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd
Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty2 Cl3 Fed Spec Single Treatment Response Overall
Unf
80205-nas1204 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1204-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.