

P/N NAS1204-7

Description

length: 0.754", thread: 1/4-28, close tolerance, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS12047

Minimum Qty (MOQ): 25

NSN: 5305-00-802-9986

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS1204-7 Specifications

| 3a |
|--|
| Right-hand |
| 0.316 Inches Minimum |
| 0.739 Inches Minimum And 0.769 Inches Maximum |
| Flat Countersunk |
| 0.449 Inches Minimum And 0.507 Inches Maximum |
| 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Cross Recess Type 1 |
| 0.250 Inches |
| 0.438 Inches Nominal |
| 28 |
| 160000 Pounds Per Square Inch |
| 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall |
| Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd |
| Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Cadmium Overall And Chromate Overall |
| Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Unf |
| 80205-nas1204 Professional/industrial Association Standard |
| |

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1204-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.