

P/N NAS1205-38

Description

Fastener Length: 2-3/4", Thread: 1/4-24, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS120538
Minimum Qty (MOQ): 5 EA

NSN: 5305-00-900-4402

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1205-38 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.350 Inches Minimum And 0.400 Inches Maximum
Fastener Length:	2.735 Inches Minimum And 2.765 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.577 Inches Minimum And 0.635 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Grip Length:	2.365 Inches Minimum And 2.385 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1205 Professional/industrial Association Standard

How to Order

Order this fine thread screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS1205-38 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.