

P/N NAS1205-38D

Description

Fastener Length: 2-3/4", Thread: 1/4-24, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS120538D

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-078-9691

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1205-38D Specifications

| Thread Class: | 3a |
|---|--|
| Thread Direction: | Right-hand |
| | |
| Thread Length: | 0.350 Inches Minimum And 0.400 Inches Maximum |
| Fastener Length: | 2.735 Inches Minimum And 2.765 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.577 Inches Minimum And 0.635 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 2.365 Inches Minimum And 2.385 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 2.606 Inches Minimum First Hole And 2.656 Inches Maximum First Hole |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1205 Professional/industrial Association Standard |

How to Order

Order this fine thread screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS1205-38D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.