

Description

Fastener Length: 53/64", Thread: 1/4-A24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12057D
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-383-6097
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1205-7D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Nominal
Fastener Length:	0.798 Inches Minimum And 0.828 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.304 Inches Minimum And 0.314 Inches Maximum
Grip Diameter:	0.3106 Inches Minimum And 0.3112 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum Grip And 0.086 Inches Maximum Grip
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum Overall And 0.086 Inches Maximum Overall
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Thread Quantity Per Inch:	A24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.994 Inches Nominal Bearing Surface Of Head
Material:	Steel Overall
Thread Series Designator:	Unjf

How to Order

Order this fine thread screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1205-7D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.