

Description

Fastener Length: 53/64", Thread: 1/4-A24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS12057D |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-383-6097 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N NAS1205-7D Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.375 Inches Nominal |
| Fastener Length: | 0.798 Inches Minimum And 0.828 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.304 Inches Minimum And 0.314 Inches Maximum |
| Grip Diameter: | 0.3106 Inches Minimum And 0.3112 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Minimum Grip And 0.086 Inches Maximum Grip |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Minimum Overall And 0.086 Inches Maximum Overall |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Thread Quantity Per Inch: | A24 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.994 Inches Nominal Bearing Surface Of Head |
| Material: | Steel Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this fine thread screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1205-7D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.