

P/N NAS1206-12

Description

Fastener Length: 1-5/32", Thread: 3/8-24, Thread Length: 13/32", NAS1206 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS120612

Minimum Qty (MOQ): 5

NSN: 5305-00-815-9423

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N NAS1206-12 Specifications

3a
Right-hand
0.366 Inches Minimum And 0.416 Inches Maximum
1.126 Inches Minimum And 1.156 Inches Maximum
Flat Countersunk
0.704 Inches Minimum And 0.762 Inches Maximum
0.3735 Inches Minimum And 0.3745 Inches Maximum
Cross Recess Type 1
0.375 Inches
0.740 Inches Minimum And 0.760 Inches Maximum
24
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd
Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Unf
80205-nas1206 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS1206-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.