

Description

Fastener Length: 2-1/64", Thread: 3/8-24, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS120626 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-00-061-5019 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1206-26 Specifications

| | |
|-------------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.331 Inches Minimum |
| Fastener Length: | 2.016 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.704 Inches Minimum And 0.762 Inches Maximum |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 1.615 Inches Minimum And 1.635 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1206 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1206-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.