

P/N NAS1207-22

Description

Fastener Length: 1-53/64", Thread: 3/8-20, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS120722

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-825-2457

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1207-22 Specifications

3a
Right-hand
0.428 Inches Minimum And 0.478 Inches Maximum
1.813 Inches Minimum And 1.843 Inches Maximum
Flat Countersunk
0.832 Inches Minimum And 0.890 Inches Maximum
0.4360 Inches Minimum And 0.4370 Inches Maximum
Cross Recess Type 1
0.437 Inches
1.365 Inches Minimum And 1.385 Inches Maximum
20
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
99.0 Degrees Minimum And 101.0 Degrees Maximum
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd
Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Unf
80205-nas1207 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS1207-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.