

Description

Length: 1-29/64", cable tie

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS1211C10 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5340-00-445-0095 |
| Schedule B: | 7307.19.9080 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1211C10 Specifications

| | |
|---------------------------|---|
| Overall Length: | 1.460 Inches Nominal |
| Inside Width: | 1.060 Inches Minimum And 1.320 Inches Maximum |
| Inside Length: | 1.000 Inches Nominal |
| Outside Width: | 1.650 Inches Nominal |
| Painted Feature: | Not Included |
| Special Features: | 18 Maximum Weight Lbs; For Use With A 1.000 In. Strap Width; Heat Treat To 160,000 Psi Minimum |
| Special Features: | .18 Maximum Weight Lbs; For Use With A 1.000 In. Strap Width; Heat Treat To 160,000 Psi Minimum |
| Material: | Steel, Mil-s-6758 |
| Material: | Steel Comp 4130 |
| Surface Treatment: | Cadmium And Chromate |
| Style Designator: | Delta |
| Surface Treatment: | Cadmium, Qq-p-416, Type 2, Class 3 |

How to Order

Order this electrical component tiedown strap from our inventory online by visiting <https://military-fasteners.com/electrical/electrical+component+tiedown+straps/NAS1211C10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.