

Description

Fastener Length: 5/16", Thread: 4-40, Thread Length: 5/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS121604E5
Minimum Qty (MOQ):	1
NSN:	5305-00-500-2134
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1216-04E5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.247 Inches Minimum And 0.327 Inches Maximum
Fastener Length:	0.297 Inches Minimum And 0.327 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.058 Inches Minimum And 0.068 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5735 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1216 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1216-04E5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.