

**Description**

Fastener Length: 1-1/8", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 1-1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS12163E18H
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-288-9544
Schedule B:	7318.15.6080
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS1216-3E18H Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.140 Inches Maximum
<b>Fastener Length:</b>	1.140 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.374 Inches Maximum
<b>Head Height:</b>	0.125 Inches Maximum
<b>Hole Diameter:</b>	0.045 Inches Nominal
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Hole Quantity:</b>	1
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Head Hole Configuration Style:</b>	Round
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1216 Professional/Industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1216-3E18H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.