

Description

Fastener Length: 1-1/8", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12163E18H
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-288-9544
Schedule B:	7318.15.6080
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1216-3E18H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.140 Inches Maximum
Fastener Length:	1.140 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.374 Inches Maximum
Head Height:	0.125 Inches Maximum
Hole Diameter:	0.045 Inches Nominal
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1216 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1216-3E18H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.