

Description

Fastener Length: 29/64", Thread: 10-32, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS12163E7 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-00-500-1426 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1216-3E7 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.361 Inches Minimum And 0.453 Inches Maximum |
| Fastener Length: | 0.423 Inches Minimum And 0.453 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.360 Inches Minimum And 0.374 Inches Maximum |
| Head Height: | 0.115 Inches Minimum And 0.125 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5735 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1216 Professional/Industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1216-3E7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.