

**Description**

Fastener Length: 37/64", Thread: 10-32, Thread Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS12163E9
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-524-4092
Schedule B:	7318.15.6080
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N NAS1216-3E9 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.484 Inches Minimum And 0.593 Inches Maximum
<b>Fastener Length:</b>	0.546 Inches Minimum And 0.593 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.360 Inches Minimum And 0.374 Inches Maximum
<b>Head Height:</b>	0.115 Inches Minimum And 0.125 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1216 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1216-3E9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.