

Description

Fastener Length: 3/4", Thread: 1/4-28, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12164E12
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-465-6303
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1216-4E12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Fastener Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.477 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.140 Inches Minimum And 0.150 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Ams,5731 Assn Std Single Material Response Or Ams,5732&jgaams,5737 A-286 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Special Features:	Proc Spec Nas4002
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1216-4E12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.