

## P/N NAS1216-4E12

### **Description**

Fastener Length: 3/4", Thread: 1/4-28, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS12164E12

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-465-6303

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1216-4E12 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Fastener Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.477 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.140 Inches Minimum And 0.150 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Ams,5731 Assn Std Single Material Response Or Ams,5732&jgaams,5737 A-286 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
Special Features:	Proc Spec Nas4002
Thread Series Designator:	Unjf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1216-4E12">https://military-fasteners.com/screws/machine+screws/NAS1216-4E12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.