

**Description**

Fastener Length: 3/4", Thread: 6-32, Thread Length: 1/4",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1218068
Minimum Qty (MOQ):	5
NSN:	5305-00-728-1405
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



## P/N NAS1218-06-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.277 Inches Minimum
<b>Fastener Length:</b>	0.777 Inches Nominal
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.256 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.087 Inches Minimum And 0.097 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-nas1218 Professional/Industrial Association Standard

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1218-06-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.