

Description

Fastener Length: 29/32", Thread: 6-32, Thread Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS121806E10
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-211-9352
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1218-06E10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.252 Inches Minimum And 0.302 Inches Maximum
Fastener Length:	0.887 Inches Minimum And 0.917 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5732 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1218 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1218-06E10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.