

Description

Fastener Length: 1-25/32", Thread: 8-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12180823
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-273-1617
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1218-08-23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.314 Inches Minimum And 0.364 Inches Maximum
Fastener Length:	1.762 Inches Minimum And 1.792 Inches Maximum
Head Style:	Pan
Head Diameter:	0.308 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	35.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1218 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1218-08-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.