

Description

Fastener Length: 17/32", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12183E3
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-324-6604
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1218-3E3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.314 Inches Minimum And 0.364 Inches Maximum
Fastener Length:	0.512 Inches Minimum And 0.542 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.360 Inches Minimum And 0.374 Inches Maximum
Head Height:	0.115 Inches Minimum And 0.125 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5732 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1218 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1218-3E3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.