

**Description**

Fastener Length: 23/32", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS12183E6
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-205-3919
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1218-3E6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.314 Inches Minimum And 0.364 Inches Maximum
<b>Fastener Length:</b>	0.699 Inches Minimum And 0.729 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.360 Inches Minimum And 0.374 Inches Maximum
<b>Head Height:</b>	0.115 Inches Minimum And 0.125 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5732 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1218 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1218-3E6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.