

Description

Fastener Length: 31/64", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12183V2
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-372-6339
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS1218-3V2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum And 0.380 Inches Maximum
Fastener Length:	0.448 Inches Minimum And 0.495 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Titanium Alloy Uns R56400
Screw Material Document And Classification:	Ams4928 Assn Std Single Material Response
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1218-3V2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.