

Description

Fastener Length: 29/32", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12183V9
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-108-0035
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS1218-3V9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.314 Inches Minimum And 0.364 Inches Maximum
Fastener Length:	0.886 Inches Minimum And 0.916 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.360 Inches Minimum And 0.374 Inches Maximum
Head Height:	0.115 Inches Minimum And 0.125 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Titanium Alloy Uns R54520
Screw Material Document And Classification:	Ams 4967 Assn Std Single Material Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1218 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1218-3V9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.