

**Description**

Fastener Length: 2-11/16", Thread: 1/4-28, Thread Length: 7/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS12184E36
Minimum Qty (MOQ):	1
NSN:	5305-01-105-7192
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1218-4E36 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.401 Inches Minimum And 0.451 Inches Maximum
<b>Fastener Length:</b>	2.661 Inches Minimum And 2.691 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.477 Inches Minimum And 0.492 Inches Maximum
<b>Head Height:</b>	0.140 Inches Minimum And 0.150 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Or Ams 5732 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1218 Professional/Industrial Association Standard

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1218-4E36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.