

## P/N NAS1218-5-4P

## **Description**

Fastener Length: 3/4", Thread: 1/4-24, Thread Length: 1/2", NAS1218 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS121854P

Minimum Qty (MOQ): 10

NSN: 5305-00-949-3829

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







# P/N NAS1218-5-4P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.361 Inches Minimum And 0.511 Inches Maximum
Fastener Length:	0.704 Inches Minimum And 0.751 Inches Maximum
Head Style:	Pan
Head Diameter:	0.594 Inches Minimum And 0.615 Inches Maximum
Head Height:	0.203 Inches Minimum And 0.218 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1218-5-4P">https://military-fasteners.com/bolts/machine+bolts/NAS1218-5-4P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.