

Description

pan head, torque set

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1218R08E13
Minimum Qty (MOQ):	10
NSN:	5305-01-365-0867
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1218R08E13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Nominal
Fastener Length:	1.136 Inches Minimum And 1.166 Inches Maximum
Head Style:	Pan
Head Diameter:	0.308 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Torque-set Ribbed
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5737 Assn Std Single Material Response Or Ams 5732 Assn Std Single Material Response Or Ams 5731 Assn Std Single Material Response
Bearing Surface Of Head Surface Finish:	32.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1218 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1218R08E13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.