

**Description**

Fastener Length: 27/32", Thread: 8-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1218R08E8                              |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-365-0866                          |
| Schedule B:             | 7318.15.2010                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1218R08E8 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                               | 3a   |
| <b>Thread Direction:</b>                           | Right-hand   |
| <b>Thread Length:</b>                              | 0.338 Inches Nominal   |
| <b>Fastener Length:</b>                            | 0.824 Inches Minimum And 0.854 Inches Maximum  |
| <b>Head Style:</b>                                 | Pan  |
| <b>Head Diameter:</b>                              | 0.308 Inches Minimum And 0.322 Inches Maximum  |
| <b>Head Height:</b>                                | 0.105 Inches Minimum And 0.115 Inches Maximum  |
| <b>Internal Drive Style:</b>                       | Torque-set Ribbed  |
| <b>Nominal Thread Diameter:</b>                    | 0.164 Inches   |
| <b>Thread Quantity Per Inch:</b>                   | 32   |
| <b>Minimum Tensile Strength:</b>                   | 160000 Pounds Per Square Inch  |
| <b>Screw Material:</b>                             | Iron Alloy 660   |
| <b>Screw Material Document And Classification:</b> | Ams 5737 Assn Std Single Material Response Or Ams 5732 Assn Std Single Material Response Or Ams 5731 Assn Std Single Material Response |
| <b>Bearing Surface Of Head Surface Finish:</b>     | 32.0 Microinches   |
| <b>Shank Surface Finish:</b>                       | 32.0 Microinches   |
| <b>Thread Surface Finish:</b>                      | 32.0 Microinches   |
| <b>Thread Series Designator:</b>                   | Unjc   |
| <b>Specification/standard Data:</b>                | 80205-nas1218 Professional/Industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1218R08E8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.