



Military-Fasteners.com

P/N NAS1218R08V2

Description

Fastener Length: 15/32", Thread: 8-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1218R08V2 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-333-4694 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1218R08V2 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.339 Inches Nominal |
| Fastener Length: | 0.449 Inches Minimum And 0.479 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.308 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Internal Drive Style: | Torque-set Ribbed |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Titanium Alloy |
| Screw Material Document And Classification: | Nas621 Assn Std Single Material Response |
| Bearing Surface Of Head Surface Finish: | 32.0 Microinches |
| Shank Surface Finish: | 32.0 Microinches |
| Thread Surface Finish: | 32.0 Microinches |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1218 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1218R08V2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.