

**Description**

Fastener Length: 17/32", Thread: 8-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1218R08V3
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-337-5026
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N NAS1218R08V3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.339 Inches Nominal
<b>Fastener Length:</b>	0.512 Inches Minimum And 0.542 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.308 Inches Minimum And 0.322 Inches Maximum
<b>Head Height:</b>	0.105 Inches Minimum And 0.115 Inches Maximum
<b>Internal Drive Style:</b>	Torque-set Ribbed
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Navy Special Project
<b>Screw Material:</b>	Titanium Alloy
<b>Screw Material Document And Classification:</b>	Nas621 Assn Std Single Material Response
<b>Bearing Surface Of Head Surface Finish:</b>	32.0 Microinches
<b>Shank Surface Finish:</b>	32.0 Microinches
<b>Thread Surface Finish:</b>	32.0 Microinches
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas1218 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1218R08V3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.