

Description

Fastener Length: 61/64", Thread: 10-32, Thread Length: 55/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1219315P
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-070-7092
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS1219-3-15P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.778 Inches Minimum And 0.870 Inches Maximum
Fastener Length:	0.923 Inches Minimum And 0.953 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.344 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Screw Material:	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1219 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1219-3-15P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.