

P/N NAS1219-3-16

Military-Fasteners.com

Description

Fastener Length: 0-63/64", Thread: 10-32, Thread Length: 59/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1219316
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-014-1149
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1219-3-16 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.840 Inches Minimum And 0.932 Inches Maximum
Fastener Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.344 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1219 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS1219-3-16</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.