

Description

Fastener Length: 1-5/8", Thread: 1/4-28, Thread Length: 1-33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12194E26
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-169-6383
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1219-4E26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.367 Inches Minimum And 1.530 Inches Maximum
Fastener Length:	1.610 Inches Minimum And 1.640 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.461 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5732 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1219 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1219-4E26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.