

Description

Fastener Length: 0-63/64", Thread: 3/8-24, Thread Length: 27/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1219616L
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-170-6150
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1219-6-16L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.674 Inches Minimum And 0.849 Inches Maximum
Fastener Length:	0.985 Inches Minimum And 1.015 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.703 Inches Minimum And 0.763 Inches Maximum
Locking Feature:	Strip Threads Or Pellet Threads Or Patch Threads
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Plastic Locking Feature
Material:	Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1219 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1219-6-16L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.