

## Description

Fastener Length: 23/64", Thread: 4-40, Thread Length: 7/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1221R04E2
Minimum Qty (MOQ):	1
NSN:	5305-01-592-8356
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



## P/N NAS1221R04E2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.232 Inches Nominal
<b>Fastener Length:</b>	0.343 Inches Minimum And 0.373 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.225 Inches Maximum
<b>Internal Drive Style:</b>	Torque-set Ribbed
<b>End Item Identification:</b>	Guidance Section, Harpoon 3779as1102-1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, 100 Degree Flush Head
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Surface Treatment:</b>	Passivate
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1221R04E2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.