

**Description**

Fastener Length: 1-3/32", Thread: 8-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS1221R08E12                 |
| Minimum Qty (MOQ):      | 10 EA                         |
| NSN:                    | 5305-01-592-8897              |
| Schedule B:             | 7318.15.8085                  |
| ECCN:                   | 9A991                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE  
AVAILABLE

## P/N NAS1221R08E12 Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                             | 3a   |
| <b>Thread Direction:</b>                         | Right-hand                                     |
| <b>Thread Length:</b>                            | 0.339 Inches Nominal                           |
| <b>Fastener Length:</b>                          | 1.074 Inches Minimum And 1.104 Inches Maximum  |
| <b>Head Style:</b>                               | Flat Countersunk                               |
| <b>Head Diameter:</b>                            | 0.294 Inches Minimum And 0.332 Inches Maximum  |
| <b>Internal Drive Style:</b>                     | Torque-set Ribbed                              |
| <b>End Item Identification:</b>                  | Guidance Section Harpoon 3779as1102-1          |
| <b>Nominal Thread Diameter:</b>                  | 0.164 Inches                                   |
| <b>Thread Quantity Per Inch:</b>                 | 32   |
| <b>Minimum Tensile Strength:</b>                 | 160000 Pounds Per Square Inch                  |
| <b>Countersink Angle:</b>                        | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| <b>Part Name Assigned By Controlling Agency:</b> | Bolt 100 Degrees Flush Head                    |
| <b>Screw Material:</b>                           | Iron Alloy 660                                 |
| <b>Screw Surface Treatment:</b>                  | Passivate                                      |
| <b>Thread Series Designator:</b>                 | Unjc   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1221R08E12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.