

P/N NAS1221R08E4

Description

Fastener Length: 19/32", Thread: 8-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1221R08E4

Minimum Qty (MOQ): 20 EA

NSN: 5305-01-365-0862

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1221R08E4 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.338 Inches Nominal |
| Fastener Length: | 0.574 Inches Minimum And 0.604 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.294 Inches Minimum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5731 Assn Std Single Material Response Or Ams 5732 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1221 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1221R08E4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.