

Description

Fastener Length: 29/32", Thread: 8-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1221R08E9
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-592-8922
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS1221R08E9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.339 Inches Nominal
Fastener Length:	0.886 Inches Minimum And 0.916 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.294 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Torque-set Ribbed
End Item Identification:	Guidance Section Harpoon 3779as1102-1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt 100 Degrees Flush Head
Screw Material:	Iron Alloy 660
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1221R08E9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.