

Description

Fastener Length: 1-27/32", Thread: 8-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS1221R08V24 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-315-2438 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



* See page 2 for technical characteristics

P/N NAS1221R08V24 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.314 Inches Minimum And 0.364 Inches Maximum |
| Fastener Length: | 1.824 Inches Minimum And 1.854 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.294 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Torque-set Ribbed |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Titanium Alloy Uns R56400 |
| Screw Material Document And Classification: | Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response |
| Bearing Surface Of Head Surface Finish: | 32.0 Microinches |
| Shank Surface Finish: | 32.0 Microinches |
| Thread Surface Finish: | 32.0 Microinches |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1221 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1221R08V24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.