

Description

Fastener Length: 25/32", Thread: 8-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1221R08V7
Minimum Qty (MOQ):	30 EA
NSN:	5305-01-314-5138
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS1221R08V7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Nominal
Fastener Length:	0.7605 Inches Minimum And 0.7905 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.294 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Torque-set Ribbed
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Titanium Alloy Uns R56400
Screw Material Document And Classification:	Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response
Bearing Surface Of Head Surface Finish:	32.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1221 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1221R08V7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.