

Description

Fastener Length: 31/32", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1221R3E10
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-590-5351
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS1221R3E10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Nominal
Fastener Length:	0.949 Inches Minimum And 0.979 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.344 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt 100 Degrees Flush Head Self-locking Optional
Screw Material:	Iron Alloy 660
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1221R3E10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.