



★ FASTENERS

Military-Fasteners.com

P/N NAS1223C1

Description

NAS1223C1 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1223C1
Minimum Qty (MOQ):	5
NSN:	5306-01-548-2245
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1223C1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Nominal
Fastener Length:	0.385 Inches Minimum And 0.415 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5735 Assn Std 1st Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1223C1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.