



Military-Fasteners.com

P/N NAS1223C2L

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1223C2L
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-757-3857
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1223C2L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Minimum And 0.348 Inches Maximum
Fastener Length:	0.463 Inches Nominal
Head Style:	Hexagon
Head Height:	0.095 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Special Features:	Soft Material Strip Insert In Thd Portion For Locking Feature
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1223 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1223C2L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.